RM14604 QUICK INSTALLATION GUIDE



Top Cover Opening

Remove one screw on the top and two screws both sides as shown Press down Thumb finger indentation located at two sides, then slide the top cover back and lift up to remove it. This unit must be operated with the chassis TOP COVER installed to ensure proper cooling 1

Installing Backplane Assembly

1. Install backplane vertically into the chassis to align the screw holes with the hooks. 2. Secure the backplane with three screws as shown.



Installing Power Supply

1. Attach the PSU bracket (base) on the chassis bottom and secure the bracket with three screws as shown (from outer to inner)

CHENBRO www.chenbro.com

- 2. Install the PSU into chassis and ensure that alignment screws holes and bracket match up. (Note: PSU has been bundled with bracket from PSU vendor already) (3)
- 3. Secure the PSU with two screws on the chassis bottom 4. Secure the PSU with three screws on the rear window. (2) 1) D.

Installing PCI Riser Card

- 1. Attach PCI riser card on the PCI retention and secure it with two screws.
- 2. Firmly press the PCI card to the riser card until PCI slot opening aligned.
- Attach PCI card and secure it with one screw.
 Firmly press the PCI card into 6th PCI expansion slot on the M/B.



- (5
- Follow quick installing guide on the HDD tray
 Engage two embossed pin into the side dimples on the HDD as shown.
- 3. Carefully push down the other side of HDD until another two embossed pin and
- side dimples lock into place.
- 4. With the lever open, insert the hard disk drive assembly into the chassis opening and push until the locking lever engaged.
- Push in the lever to lock it into place